


TANK DRY WEIGHT APPROX. 30KGS











NOTE:-IF TANK HAS A SIDE MANWAY BOLTS TO BE TIGHTENED USING TORQUE WRENCH SET AT 95Nm

CUSTOMER TO RE-TORQUE DURING ON SITE HYDROSTATIC TEST

FABRICATION NOTES

NOTE:- ALL PLASTIC TANKS TO BE LIFTED USING SUITABLY RATED LIFTING BEAM

NOTES:

1. ALL NOZZLES UPTO AND INCLUDING 110MM TO HAVE 3 OFF 10MM THK GUSSETS 100X100.

2. ALL CUT EDGES TO BE PLANED AND SCRAPED.

3. ALL PEN MAKEN TO BE REMOVED.

4. AFFER YEROKTEST ALL NOZZLES TO BE BLANKED OFF USING FULLOW FE CASH.

GENERAL TOLERANCE + 10mm - 10mm
DENIGRO COPE
DENIND PRODUCED LISING AUTOCESX
INVESTOR
DO NOT ALTER MANIALLY
DD NOT SCALE - IF IN DOUBT ASK
ALL DIMENSIONS IN MILLIMETRES UNLESS STATED
ALWAYS REFER TO PLAN YEW
FOR CORRECT ORIENTATION
ALL WELDS TO BE
FOR CODE
ALL WISELSS TO BE
FOR CODE
ALL WISELS STATED
ALL WISELS TO BE
FOR CODE
ALL WISELS STATED
ALL WISE